





材 质：外层 软质、阻燃、环保、无卤、
 照射交连 复合物制成
 内 层：高性能热熔胶制成
 特 性：对金属 塑胶有良好粘着效果 完全防水密封
 防腐 耐磨 可直接埋入地底
 适用温度： 至 ；起始收缩温度 完成收
 缩
 使用方法：使用热风枪加热即可收缩
 用 途：应用于接线防水 防漏气 电线分支密封固定
 或修补 金属管防腐
 颜 色：黑
 收缩比率：



SCM-01	±	±	±
SCM-02	±	±	±
SCM-03S	±	±	±
SCM-03L	±	±	±
SCM-04	±	±	±
SCM-05	±	±	±
SCM-06	±	±	±
SCM-07	±	±	±
SCM-11	±	±	±
SCM-13	±	±	±
SCM-15	±	±	±
SCM-17	±	±	±
SCM-20	±	±	±
SCM-23	±	±	±
SCM-27	±	±	±
SCM-35	±	±	±
SCM-40	±	±	±
SCM-50	±	±	±



W3F2-1/8	±	±
W3F2-3/16	±	±
W3F2-1/4	±	±
W3F2-5/16	±	±
W3F2-3/8	±	±
W3F2-1/2	±	±
W3F2-5/8	±	±
W3F2-3/4	±	±
W3F2-1	±	±
W3F2-1-1/4	±	±
W3F2-1-1/2	±	±