

**ZODZ.E306674
Positioning Devices**[Page Bottom](#)**Positioning Devices**[See General Information for Positioning Devices](#)**SHANGHAI RICHENG ELECTRONICS CO LTD**

E306674

9 PINGLIN RD
XINSHEN INDUSTRIAL AREA
FENGXIAN DISTRICT
201417 SHANGHAI, CHINA

Trademark and/or Tradename: "RCCN",

Cable ties, Cat. Nos. G80M, G90M, G100M, G120M, G140M, G150M, G160M, G200M, G250M, G300M, G120ST, G150ST, G160ST, G190ST, G200ST, G215ST, G250ST, G265ST, G280ST, G300ST, G370ST, G390ST, G430ST, G450ST, G530ST, G550ST, G635ST, G685ST, G120I, G140I, G150I, G180I, G200I, G215I, G250I, G300I, G370I, G150HD, G200HD, G250HD, G300HD, G370HD, G430HDS, G450HDS, G530HDS, G630HDS, GE430HD, G230EHD, G290EHD, G380EHD, G480EHD, G580EHD, G730EHD, G880EHD, G1030EHD, for indoor use not to exceed 85°C.

Cat. Nos. G150HDUV, G120STUV, G150STUV, G160STUV, G190STUV, G200STUV, G215STUV, G250STUV, G265STUV, G280STUV, G300STUV, G370STUV, G390STUV, G430STUV, G450STUV, G530STUV, G550STUV, G635STUV, G685STUV, G80MUJ, G90MUJ, G100MUJ, G120MUJ, G140MUJ, G150MUJ, G160MUJ, G200MUJ, G250MUJ, G300MUJ, G140IUV, G150IUV, G180IUV, G200IUV, G215IUV, G250IUV, G300IUV, G370IUV, G200HDUV, G250HDUV, G300HDUV, G370HDUV, G430HDSUV, G450HDSUV, G530HDSUV, G630HDSUV, GE430HDUV, G230EHDUV, G290EHDUV, G380EHDUV, G480EHDUV, G580EHDUV, G730EHDUV, G880EHDUV, E1030EHDUV, for indoor or outdoor use not to exceed 85°C.

Mountable cable ties, Cat. Nos. TCV-110M, TCV-150I, TCV-205ST, TCV-200ST, TCV-300ST, TCV-370ST, TCV-200HD, TCV-300HD, TCV-380HD, for indoor use not to exceed 85°C.

Cat. Nos. TCV-200STUV, TCV-300STUV, TCV-370STUV, TCV-110MUJ, TCV-150IUV, TCV-205STUV, TCV-200HDUV, TCV-300HDUV, TCV-380HDUV, for indoor or outdoor use not to exceed 85°C.

Push mount cable ties, Cat. Nos. PWV-110M, PWV-110MA, PVW-130M, PVW-130MA, PVW-130I, PVW-130IA, PCV-150I, PWV-130ST, PWV-170ST, PWV190ST, PCV-200ST, for indoor use not to exceed 85°C.

Cat. Nos. PWV-110MUJ, PWV-110MAUV, PVW-130MUJ, PVW-130MAUV, PVW-130IUV, PVW-130IAUV, PCV-150IUV, PWV-130STUV, PWV-170STUV, PWV-190STUV, PCV-200STUV, for indoor or outdoor use not to exceed 85°C.

Releasable cable ties, Cat. Nos. HV-100HD, HV-120HD, HV-150HD, HV-200HD, HV-250HD, HV-300HD, HV-370HD, RCV-140I, RCV-200ST, RCV-300ST, RCV-370ST, RCV-430ST, for indoor use not to exceed 85°C.

Cat. Nos. HV-100HDUV, HV-120HDUV, HV-150HDUV, HV-200HDUV, HV-250HDUV, HV-300HDUV, HV-370HDUV, RCV-140IUV, RCV-200STUV, RCV-300STUV, RCV-370STUV, RCV-430STUV, for indoor or outdoor use not to exceed 85°C.

Marker cable ties, Cat. Nos. MCV-110, MCV-210S, MCV-200S, MCV-100, MCV1-190, MCV1-220, MCV1-270, MCV1-300, MCV1-370, MCV1-190L, MCV1-220L, MCV1-270L, MCV1-300L, MCV1-370L, for indoor use not to exceed 85°C.

[Last Updated](#) on 2012-10-01[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

2012 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".