


# 日成 型尼龙米字头螺丝



材质：UL合格之NYLON66(本色)，防火等级94V-2，绝缘性佳，不易老化。  
 用途：PC板，机板及其它产品固定用。  
 特点：质量轻，绝缘，抗干扰，不生锈，耐酸碱，耐候性强。  
 说明：本品与NCRS型区别头部槽状为米字型，参考3D图。  
 Material：UL approved NYLON66(natural)，Fireproof:94V-2，good insulation, good aging resistant

单位/Unit:mm

型号	螺牙				包装
	Thread				
	M3	4	6.0	2.4	1000pcs
	M3	5	6.0	2.4	
	M3	6	6.0	2.4	
	M3	7	6.0	2.4	
	M3	8	6.0	2.4	
	M3	10	6.0	2.4	
	M3	12	6.0	2.4	
	M3	16	6.0	2.4	
	M3	20	6.0	2.4	
	M3	25	6.0	2.4	
	M3	30	6.0	2.4	
	M3	35	6.0	2.4	
	M3	40	6.0	2.4	
	M4	6	8.0	3.1	
	M4	8	8.0	3.1	
	M4	10	8.0	3.1	
	M4	12	8.0	3.1	
	M4	16	8.0	3.1	
	M4	20	8.0	3.1	
	M4	25	8.0	3.1	
	M4	30	8.0	3.1	
	M4	40	8.0	3.1	

单位/Unit:mm

型号	螺牙				包装
	Thread				
	M5	8	9.5	3.7	1000pcs
	M5	10	9.5	3.7	
	M5	12	9.5	3.7	
	M5	16	9.5	3.7	
	M5	20	9.5	3.7	
	M5	25	9.5	3.7	
	M5	30	9.5	3.7	
	M5	40	9.5	3.7	
	M5	50	9.5	3.7	
	M6	6.5	12	4.6	
	M6	8	12	4.6	
	M6	10	12	4.6	
	M6	12	12	4.6	
	M6	16	12	4.6	
	M6	20	12	4.6	
	M6	25	12	4.6	
	M6	30	12	4.6	
	M6	40	12	4.6	
	M6	50	12	4.6	
	M6	60	12	4.6	

